


1/8 cell structural core faced with 1/8 HDF.

ADVANTAGES

- With this high density structural core, lightweight panels are taken to the next level
- Easily apply face materials (veneer, laminate, and coatings)
- Finish with a variety of edge options
- Rigid face material supports selected methods of attachment
- Optional skin thicknesses are available

SIZES AVAILABLE

- 3/4"x49x97
- 1"x49x97
- 1-1/4"x49x97
- 1-1/2"x49x97
- 1-3/4"x49x97
- 2"x49x97
- 3/4"x49x121
- 1"x49x121
- 1-1/4"x49x121
- 1-1/2"x49x121
- 1-3/4"x49x121
- 2"x49x121





TECHNICAL DATA

	MATERIAL THICKNESS									
	3/4"	1"	1-1/4"	1-1/2"	1-3/4"	2"				
SKIN THICKNESS	0.118"	0.118"	-	0.118"	0.118"	0.118"				
CORE THICKNESS	0.514"	0.764"	-	1.264"	1.514"	1.764"				
MAX SCREW WITHDRAWN FORCE, LBF	78	87	-	81	-	-				
MAX SCREW TENSILE FORCE, LBF	130	213	-	230	-	-				
MAX TENSILE STRENGTH, PSI	32	52	-	56	-	-				
COMP, STRENGTH @5% STRAIN, PSI	139	125	-	123	-	-				
MAX FLEXURE FORCE, LBF	233	264	-	254	-	-				
MODULUS OF RUPTURE, PSI	3481	2901	-	1886	-	-				
MODULUS OF ELASTICITY, PSI	310821	248889	-	214079	-	-				
WEIGHT PER PANEL, LB** (49 x 97)	51	56	-	68	73	79				

PACKAGING QUANTITY PER SKID

	MATERIAL THICKNESS								
SHEET SIZE	3/4"	1"	1-1/4"	1-1/2"	1-3/4"	2"			
49 X 97	64	48	38	32	27	24			

^{*} Testing conducted with Varianta Screw HC 013.30.900

^{**} Actual measured weight may vary due to temperature and humidity. Weight provided is for comparative analysis only

